



Portable Heat Pump Air Conditioners

20ACH 3612

| | | |
|-----------------------------------|--|----------------|
| Cooling Capacity | @ARI 80°F-67°F at 52% Relative Humidity | 3 Ton - 36,050 |
| Heating Capacity | @ARI 70°F-60°F at 60% Relative Humidity | 32,500 |
| Dimensions | Width (Inches) | 28 |
| | Depth (Inches) | 35 |
| | Height (Inches) | 50.25 |
| | Weight (Pounds) | 365 |
| | Shipping Weight | 405 |
| | Shipping Volume (cubic feet) | 40 |
| Electrical Characteristics | Power Supply (Volts) | 208-230/1 |
| | Current Consumption | 18.1 |
| | Cooling Watts | 3620 |
| | In rush current (Amps) | 140 |
| | NEMA Plug Configuration | 6-30p |
| | EER | 10.0 |
| | Min-max Voltage | 187-253 |
| | Power Cord Gauge | 12/3 |
| | Power Cord Length (Feet) | 10 |
| Compressor Characteristics | Compressor HP | 3 |
| | Compressor RLA | 13.6 |
| | Compressor LRA | 83 |
| Evaporator | Evap (CFM) | 1200 |
| | Evap Motor HP | 1/3 |
| | Evap Motor Watts | 375 |
| Condenser Characteristics | Condenser CFM | 1390 |
| | Condenser Motor HP | 1 |
| | Condenser Motor Watts | 460 |
| Miscellaneous Features | Condensate | 5 gal. tank |
| | Sound Level | 69 |
| | R-410A Charge Oz. | 66 |



Portable Heat Pump Air Conditioners

20ACH 3612

Power Supply 208-230 volts 60 hertz 1 phase 18.1 amperes

Width 28 inches

Depth 35 inches

Height 50.25 inches

Weight (net/shipping) lbs 365/405

All models are backed by a 12-month warranty with 60 months for the compressor.

