



Portable Heat Pump Air Conditioners

20ACH 3632

Cooling Capacity	@ARI 80°F-67°F at 52% Relative Humidity	3 Ton - 36,050
Heating Capacity	@ARI 70°F-60°F at 60% Relative Humidity	32,500
Dimensions	Width (Inches)	28
	Depth (Inches)	35
	Height (Inches)	50.25
	Weight (Pounds)	365
	Shipping Weight	405
	Shipping Volume (cubic feet)	40
Electrical Characteristics	Power Supply (Volts)	208-230/3
	Current Consumption	17.2
	Cooling Watts	3620
	In rush current (Amps)	122
	NEMA Plug Configuration	L15-30p
	EER	10.0
	Min-max Voltage	187-253
	Power Cord Gauge	10/4
	Power Cord Length (Feet)	10
Compressor Characteristics	Compressor HP	3
	Compressor RLA	8.8
	Compressor LRA	77
Evaporator	Evap (CFM)	1200
	Evap Motor HP	1/3
	Evap Motor Watts	375
Condenser Characteristics	Condenser CFM	1390
	Condenser Motor HP	1
	Condenser Motor Watts	460
Miscellaneous Features	Condensate	5 gal. tank
	Sound Level	69
	R-410A Charge Oz.	66



Portable Heat Pump Air Conditioners

20ACH 3632

Power Supply 208-230 volts 60 hertz 3 phase 17.2 amperes

Width 28 inches

Depth 35 inches

Height 50.25 inches

Weight (net/shipping) lbs 365/405

All models are backed by a 12-month warranty with 60 months for the compressor.

