



Portable Heat Pump Air Conditioners

20ACH 6034

Cooling Capacity	@ARI 80°F-67°F at 52% Relative Humidity	5 Ton - 60,050
Heating Capacity	@ARI 70°F-60°F at 60% Relative Humidity	53,500
Dimensions	Width (Inches)	28
	Depth (Inches)	39
	Height (Inches)	52.25
	Weight (Pounds)	515
	Shipping Weight	555
	Shipping Volume (cubic feet)	48
Electrical Characteristics	Power Supply (Volts)	460/3
	Current Consumption	14.8
	Cooling Watts	6000
	In rush current (Amps)	140
	NEMA Plug Configuration	L16-20p
	EER	10.0
	Min-max Voltage	414-506
	Power Cord Gauge	10/4
	Power Cord Length (Feet)	10
Compressor Characteristics	Compressor HP	5
	Compressor RLA	9.0
	Compressor LRA	62
Evaporator	Evap (CFM)	1950
	Evap Motor HP	1
	Evap Motor Watts	550
Condenser Characteristics	Condenser CFM	2200
	Condenser Motor HP	1
	Condenser Motor Watts	750
Miscellaneous Features	Condensate	Pump Standard
	Sound Level	78
	R-410A Charge Oz.	80



Portable Heat Pump Air Conditioners

20ACH 6034

Power Supply 460 volts 60 hertz 3 phase 14.8 amperes

Width 28 inches

Depth 39 inches

Height 52.25 inches

Weight (net/shipping) lbs 515/555

All models are backed by a 12-month warranty with 60 months for the compressor.

