



Low Temperature Portable Air Cooled Air Conditioners

20AC 1211

Cooling Capacity	@ARI 80°F-67°F at 52% Relative Humidity	1 Ton - 11,800
Dimensions	Width (Inches)	20
	Depth (Inches)	25
	Height (Inches)	36.5
	Weight (Pounds)	180
	Shipping Weight	200
	Shipping Volume (cubic feet)	19
Electrical Characteristics	Power Supply (Volts)	115/1
	Current Consumption	10.4
	Cooling Watts	1180
	In rush current (Amps)	77.5
	NEMA Plug Configuration	5 -15p
	EER	10.0
	Min-max Voltage	105-125
	Power Cord Gauge	14/3
	Power Cord Length (Feet)	10
Compressor Characteristics	Compressor HP	1
	Compressor RLA	9.5
	Compressor LRA	50
Evaporator	Evap (CFM)	400
	Evap Motor HP	1/8
	Evap Motor Watts	180
Condenser Characteristics	Condenser CFM	580
	Condenser Motor HP	1/8
	Condenser Motor Watts	200
Miscellaneous Features	Condensate	5 gal. tank
	Sound Level	54
	R-410A Charge Oz.	18



Low Temperature Portable Air Cooled Air Conditioners

20AC 1211

Power Supply 115 volts 60 hertz 1 phase 10.4 amperes

Width 20 inches

Depth 25 inches

Height 36.5 inches

Weight (net/shipping) lbs 180/200

All models are backed by a 12-month warranty with 60 months for the compressor.

