



Low Temperature Portable Air Cooled Air Conditioners

20AC 3612

Cooling Capacity	@ARI 80°F-67°F at 52% Relative Humidity	3 Ton - 36,050
Dimensions	Width (Inches)	28
	Depth (Inches)	35
	Height (Inches)	50.25
	Weight (Pounds)	365
	Shipping Weight	405
	Shipping Volume (cubic feet)	40
Electrical Characteristics	Power Supply (Volts)	208-230/1
	Current Consumption	18.1
	Cooling Watts	3620
	In rush current (Amps)	140
	NEMA Plug Configuration	6-30p
	EER	10.0
	Min-max Voltage	187-253
	Power Cord Gauge	12/3
	Power Cord Length (Feet)	10
Compressor Characteristics	Compressor HP	3
	Compressor RLA	13.6
	Compressor LRA	83
Evaporator	Evap (CFM)	1200
	Evap Motor HP	1/3
	Evap Motor Watts	375
Condenser Characteristics	Condenser CFM	1390
	Condenser Motor HP	1
	Condenser Motor Watts	460
Miscellaneous Features	Condensate	5 gal. tank
	Sound Level	69
	R-410A Charge Oz.	66



Low Temperature Portable Air Cooled Air Conditioners

20AC 3612

Power Supply 208-230 volts 60 hertz 1 phase 18.1 amperes

Width 28 inches

Depth 35 inches

Height 50.25 inches

Weight (net/shipping) lbs 365/405

All models are backed by a 12-month warranty with 60 months for the compressor.

