



## Low Temperature Portable Air Cooled Air Conditioners

# 20AC 6034

<b>Cooling Capacity</b>	@ARI 80°F-67°F at 52% Relative Humidity	5 Ton - 60,050
<b>Dimensions</b>	Width (Inches)	28
	Depth (Inches)	39
	Height (Inches)	52.25
	Weight (Pounds)	515
	Shipping Weight	555
	Shipping Volume (cubic feet)	48
<b>Electrical Characteristics</b>	Power Supply (Volts)	460/3
	Current Consumption	14.8
	Cooling Watts	6000
	In rush current (Amps)	140
	NEMA Plug Configuration	L16-20P
	EER	10.0
	Min-max Voltage	414-506
	Power Cord Gauge	10/4
	Power Cord Length (Feet)	10
<b>Compressor Characteristics</b>	Compressor HP	5
	Compressor RLA	9.0
	Compressor LRA	62
<b>Evaporator</b>	Evap (CFM)	1950
	Evap Motor HP	1
	Evap Motor Watts	550
<b>Condenser Characteristics</b>	Condenser CFM	2200
	Condenser Motor HP	1
	Condenser Motor Watts	750
<b>Miscellaneous Features</b>	Condensate	Pump-standard 20ft. lift
	Sound Level	78
	R-410A Charge Oz.	80



## Low Temperature Portable Air Cooled Air Conditioners

# 20AC 6034

**Power Supply** 460 volts 60 hertz 3 phase 14.8 amperes

**Width** 28 inches

**Depth** 39 inches

**Height** 52.25 inches

**Weight** (net/shipping) lbs 515/555

All models are backed by a 12-month warranty with 60 months for the compressor.

