



Portable Trailer Mounted Air Conditioners

5T 208/3

Cooling Capacity	Btu/Hr @ 80° Drybulb and 67° Wetbulb Entering Air Temperature	5 Ton - 63,500
Heating Capacity	Btu/Hr	Optional
Dimensions	Width (Inches)	34
	Depth (Inches)	57
	Height (Inches)	43
	Weight (Pounds)	675
Electrical Characteristics	Power Supply (Volts)	208-230/60/3 Phase
	Power Consumption (Kilowatts)	9.3
	Current Consumption (Amperes)	35
	Service Required (Amperes)	60
	Min-max Voltage	200-240
	Power Cord Gauge	4
	Power Cord Length (Feet)	110
Evaporator Fan	Fan Type	Centrifugal
	Air Flow (CFM)	2,000
	Max. External Static Pressure (Inches Of Water Gauge)	1
	Supply/Return Flanges	1/1
	Flange Diameter (Inches)	14
	Max. Length of Ducting (Feet)	85
Compressor	Compressor Type	Hermetic Scroll
	R-22 Charge (Pounds)	13.0
	Operating Range	65°F - 115°F
Miscellaneous Features	Remote Thermostat	Optional
	Compressor Overload Relay	Optional
	Fan Motor Protection	Optional
	Anti-freeze Thermostat	Optional
	High-Pressure Switch	Yes
	Compressor Short-cycle Protection	Yes
	Accommodates Condensate Pump	Yes
	Humidity Removed @60% RH (Gallons per Hour)	2.5
	Low Pressure Switch	Yes
	Phase Protection	N/A
	Low Ambient Operation	Optional



Portable Trailer Mounted Air Conditioners

5T 208/3

Power Supply 208-230 volts 60 hertz 3 phase 35 amperes

Width 34 inches

Depth 57 inches

Height 43 inches

Weight 675 lbs

All models are backed by a 12-month parts warranty.

