



Portable Water Cooled Air Conditioners

OWC 3612

Cooling Capacity	@ARI 80°F-67°F at 52% Relative Humidity	3 Ton - 36,100
Dimensions	Width (Inches)	27.0
	Depth (Inches)	18.0
	Height (Inches)	50.25
	Weight (Pounds)	240
	Shipping Weight	270
	Shipping Volume (cubic feet)	23
Electrical Characteristics	Power Supply (Volts)	208-230/1
	Current Consumption	12.0
	Cooling Watts	2700
	In rush current (Amps)	99.5
	NEMA Plug Configuration	6-20p
	EER	13.4
	Min-max Voltage	187-253
	Power Cord Gauge	14/3
	Power Cord Length (Feet)	10
Compressor Characteristics	Compressor HP	3
	Compressor RLA	13.6
	Compressor LRA	83
Evaporator	Evap (CFM)	1200
	Evap Motor HP	1/3
	Evap Motor Watts	375
Water Connection Characteristics	Cond Water Flow (GPM) at 60°F inlet	2.2
	Cond Water Flow (GPM) at 85°F inlet	9
	Cond Coil Pressure Drop PSI	0.4
	Water Valve Pressure Drop PSI	2.0
	Water Valve Connection	5/8 MF
	Drain (Return) Connection	5/8 MF
Miscellaneous Features	Condensate Pump Lift	20 Ft.
	Sound Level	62
	R-410A Charge Oz.	24



Portable Water Cooled Air Conditioners

OWC 3612

Power Supply 208-230 volts 60 hertz 1 phase 12.0 amperes

Width 27 inches

Depth 18 inches

Height 50.25 inches

Weight (net/shipping) lbs 240/270

All models are backed by a 12-month warranty with 60 months for the compressor.

