



## Portable Water Cooled Air Conditioners

# OWC 3632

<b>Cooling Capacity</b>	@ARI 80°F-67°F at 52% Relative Humidity	3 Ton - 36,100
<b>Dimensions</b>	Width (Inches)	27.0
	Depth (Inches)	18.0
	Height (Inches)	50.25
	Weight (Pounds)	240
	Shipping Weight	270
	Shipping Volume (cubic feet)	23
<b>Electrical Characteristics</b>	Power Supply (Volts)	208-230/3
	Current Consumption	9.3
	Cooling Watts	2700
	In rush current (Amps)	88
	NEMA Plug Configuration	L15-20p
	EER	13.4
	Min-max Voltage	187-253
	Power Cord Gauge	14/4
	Power Cord Length (Feet)	10
<b>Compressor Characteristics</b>	Compressor HP	3
	Compressor RLA	8.8
	Compressor LRA	77
<b>Evaporator</b>	Evap (CFM)	1200
	Evap Motor HP	1/3
	Evap Motor Watts	375
<b>Water Connection Characteristics</b>	Cond Water Flow (GPM) at 60°F inlet	2.2
	Cond Water Flow (GPM) at 85°F inlet	9
	Cond Coil Pressure Drop PSI	0.4
	Water Valve Pressure Drop PSI	2.0
	Water Valve Connection	5/8 MF
	Drain (Return) Connection	5/8 MF
<b>Miscellaneous Features</b>	Condensate Pump Lift	20 Ft.
	Sound Level	62
	R-410A Charge Oz.	24



## Portable Water Cooled Air Conditioners

# OWC 3632

**Power Supply** 208-230 volts 60 hertz 3 phase 9.3 amperes

**Width** 27 inches

**Depth** 18 inches

**Height** 50.25 inches

**Weight** (net/shipping) lbs 240/270

All models are backed by a 12-month warranty with 60 months for the compressor.

