



Portable Water Cooled Air Conditioners

OWC 6034

Cooling Capacity	@ARI 80°F-67°F at 52% Relative Humidity	5 Ton - 60,100
Dimensions	Width (Inches)	28.25
	Depth (Inches)	39.0
	Height (Inches)	52.5
	Weight (Pounds)	520
	Shipping Weight	560
	Shipping Volume (cubic feet)	46
Electrical Characteristics	Power Supply (Volts)	460/3
	Current Consumption	6.3
	Cooling Watts	5000
	In rush current (Amps)	140
	NEMA Plug Configuration	L16-20p
	EER	12.0
	Min-max Voltage	414-506
	Power Cord Gauge	10/4
	Power Cord Length (Feet)	10
Compressor Characteristics	Compressor HP	5
	Compressor RLA	9.0
	Compressor LRA	62
Evaporator	Evap (CFM)	1950
	Evap Motor HP	1
	Evap Motor Watts	550
Water Connection Characteristics	Cond Water Flow (GPM) at 60°F inlet	5.5
	Cond Water Flow (GPM) at 85°F inlet	15
	Cond Coil Pressure Drop PSI	0.4
	Water Valve Pressure Drop PSI	2.0
	Water Valve Connection	5/8 MF
	Drain (Return) Connection	5/8 MF
Miscellaneous Features	Condensate Pump Lift	20 Ft.
	Sound Level	69
	R-410A Charge Oz.	52



Portable Water Cooled Air Conditioners

OWC 6034

Power Supply 460 volts 60 hertz 3 phase 6.3 amperes

Width 28.25 inches

Depth 39 inches

Height 52.5 inches

Weight (net/shipping) lbs 520/560

All models are backed by a 12-month warranty with 60 months for the compressor.

