



Portable Specialty Coolers Air Conditioners

Climate Pro® 18

Cooling Capacity	Btu/Hr @ 80°F at 50% Relative Humidity	14,600
Heating Capacity	Btu/Hr @ 70°F Indoors, 47° Outdoors at 57% Relative Humidity	13,700
Dimensions	Width (Inches)	21
	Depth (Inches)	27
	Height (Inches)	49
	Weight (Pounds)	214
	Shipping Weight	257
Electrical Characteristics	Power Supply (Volts)	115/1
	Power Consumption (Kilowatts)	1.54
	Current Consumption	14.1
	Fuse Size (Amperes)	20
	NEMA Plug Configuration	5 -20p
	Min-max Voltage	105-125
	Power Cord Gauge	12/3
	Power Cord Length (Feet)	10
Compressor Characteristics	Compressor Type	Hermetic Rotary
	Refrigerant	R-410A
	Operating Conditions: Min-max °F	65°-95°F @ 50% RH
	Operating Conditions (Heating): Min-max °F	40°-80°F @ 50% RH
Fan Characteristics	Evaporator:	
	Fan Type	Centrifugal
	Air Flow (CFM) High/Medium/Low	540/440/350
	Max External Static Pressure (Inches Of Water Gauge)	0.31
	Condenser:	
	Fan Type	Centrifugal
	Air Flow (CFM)	700
	Max External Static Pressure (Inches Of Water Gauge)	0.23
Safety Devices	Compressor Overload Relay	Yes
	Fan Motor Protection	Yes
	Anti-freeze Thermostat	Yes
	Automatic Tank Shut-off	Yes
	Condensate Tank Capacity (Gallons)	5
	High-pressure Switch	Yes
	Compressor Short-Cycle Protection	Yes
	Fan Mode Switch	Yes
	Automatic Restart	Yes
	Thermostat	Yes
	Control Panel	Programmable
	Thermostat Control	Digital
Miscellaneous Features	Humidity Removed @ 60% RH	0.9
	Accommodates Condensate Pump	Yes
	Sound Level (dB) High/Low	61/59
	Max Evaporator Ducting Length* (Ft)	25
	Max Condenser Ducting Length* (Ft)	100
	<i>* subtract 10 Ft For Every 90° Bend</i>	



Portable Specialty Coolers Air Conditioners

Climate Pro[®] 18

Power Supply 115 volts 60 hertz 1 phase 14.1 amperes

Width 21 inches


Depth 27 inches

Height 49 inches


Weight (net/shipping) lbs 214/257

All models are backed by a 12-month warranty with 36 months for the compressor.
All coils are treated with an acrylic resin coating for extended life and corrosion resistance.

TOP



FRONT



SIDE

