



Portable Air Cooled Air Conditioners

PAC 2412

Cooling Capacity

@ARI 80°F-67°F

2 Ton - 24,020 BTUH

Dimensions

Width (Inches)	24.00
Depth (Inches)	30.00
Height (Inches)	45.75
Weight (Pounds)	260
Shipping Weight	285
Shipping Volume (Cubic Feet)	28

Electrical Characteristics

Power Supply (Volts)	208-230/1
Current Consumption	14.9
Cooling Watts	2700
In rush current (Amps)	68
NEMA Plug Configuration	6-20P, LCDI
EER	8.9
Min-max Voltage	187-253
Power Cord Gauge	14/3
Power Cord Length (Feet)	10

Compressor Characteristics

Compressor (Rotary) HP	2
Compressor LRA	48

Evaporator

Evap (CFM)	810
Evap Motor HP	1/3
Evap Motor Watts	370

Condenser Characteristics

Condenser CFM	1010
Condenser Motor HP	1/3
Condenser Motor Watts	490

Miscellaneous Features

Condensate	5 gal. tank
Sound Level	65
R-410A Charge Oz.	37

Power Supply

208-230 volts
60 hertz 1 phase
14.9 amperes

Width

24
inches

Depth

30
inches

Height

45.75
inches

Weight

260
LBS

