



Portable Water Cooled Air Conditioners

PWC 6012

Cooling Capacity

@ARI 80°F-67°F
at 52% Relative Humidity

5 Ton - 60,100

Dimensions

Width (Inches) 27.00
Depth (Inches) 29.00
Height (Inches) 51.50
Weight (Pounds) 375
Shipping Weight 430
Shipping Volume (Cubic Feet) 35

27.00
29.00
51.50
375
430
35

Electrical Characteristics

Power Supply (Volts) 208-230/1
Current Consumption 23.7
Cooling Watts 5000
In rush current (Amps) 165
NEMA Plug Configuration 6 - 30p
EER 12.0
Min-max Voltage 187-253
Power Cord Gauge 8/3
Power Cord Length (Feet) 10

208-230/1
23.7
5000
165
6 - 30p
12.0
187-253
8/3
10

Compressor Characteristics

Compressor HP 5
Compressor RLA 27.6
Compressor LRA 158

5
27.6
158

Evaporator

Evap (CFM) 1950
Evap Motor HP 1
Evap Motor Watts 670

1950
1
670

Water Connection Characteristics

Cond Water Flow (GPM) at 60°F inlet 3.8
Cond Water Flow (GPM) at 85°F inlet 15
Water Valve Connection 5/8 MF
Drain (Return) Connection 3/8 MF

3.8
15
5/8 MF
3/8 MF

Miscellaneous Features

Condensate Pump Lift 20 ft.
Sound Level 69
R-410A Charge Oz. 52

20 ft.
69
52

Power Supply

208 - 230 volts
60 hertz 1 phase
23.7 amperes

Width

27
inches

Depth

29
inches

Height

51.50
inches

Weight

375
LBS

