



Portable Air Cooled Air Conditioners

Classic 60

Cooling Capacity	Btu/hr. @ 95°	
	At 60% Relative Humidity	60,000
Dimensions	Width (Inches)	32
	Depth (Inches)	49
	Height (Inches)	42
	Weight (Pounds)	474
	Shipping Weight	566
Electrical Characteristics	Power Supply (Volts)	460/3
	Power Consumption (Kilowatts)	5.9
	Current Consumption (Amperes)	8.8
	Fuse Size (Amperes)	20
	NEMA Plug Configuration	N/A
	Min-max Voltage	440-480 Volt
	Power Cord Gauge	N/A
Power Cord Length (Feet)	N/A	
Compressor Characteristics	Compressor Type	Hermetic Scroll
	Refrigerant	R-410A
	Operating Conditions: Min-max °F	75°-115°F, 50% RH
Fan Characteristics	<i>Evaporator:</i>	
	Fan Type	Centrifugal
	Air Flow (CFM) High/Low	1580
	Max. External Static Pressure (Inches Of Water Gauge)	1.35
	<i>Condenser:</i>	
	Fan Type	Propeller
	Air Flow (CFM) High/Low	3800
Max. External Static Pressure (Inches Of Water Gauge)	0.05	
Safety Devices	Compressor Overload Relay	Yes
	Fan Motor Protection	Yes
	Anti-freeze Thermostat	Yes
	Automatic Tank Shut-off	N/A
	Condensate Tank Capacity (Gallons)	N/A
	High-pressure Switch	Yes
	Compressor Short-cycle Protection	Yes
	Fan Mode Switch	Yes
	Automatic Restart	Yes
	Thermostat	Yes
Control Panel	Digital	
Miscellaneous Features	Operating Cost	\$0.518
	Humidity Removed @ 60% RH	3.84
	Accommodates Condensate Pump	N/A
	Sound Level (Db) High/Low	72
	Max Evaporator Ducting Length*(Ft.)	Varies
	Max Condenser Ducting Length*(Ft.)	40
<i>*subtract 10 Ft. For Every 90° Bend</i>		



Portable Air Cooled Air Conditioners

Classic 60

Power Supply 460 volts 60 hertz 3 phase 8.8 amperes

Width 32 inches

Depth 49 inches

Height 42 inches

Weight (net/shipping) lbs 474/566

All models are backed by a 12-month warranty with 36 months for the compressor.
All coils are treated with an acrylic resin coating for extended life and corrosion resistance.

