



Low Temperature Portable Air Cooled Air Conditioners

20AC 2412

Cooling Capacity	@ARI 80°F-67°F at 52% Relative Humidity	2 Ton - 24,020
Dimensions	Width (Inches)	24
	Depth (Inches)	30
	Height (Inches)	45.5
	Weight (Pounds)	260
	Shipping Weight	285
	Shipping Volume (cubic feet)	28
Electrical Characteristics	Power Supply (Volts)	208-230/1
	Current Consumption	14.9
	Cooling Watts	2700
	In rush current (Amps)	90
	NEMA Plug Configuration	6-20p
	EER	8.9
	Min-max Voltage	187-253
	Power Cord Gauge	14/3
	Power Cord Length (Feet)	10
Compressor Characteristics	Compressor HP	2
	Compressor RLA	10.5
	Compressor LRA	48
Evaporator	Evap (CFM)	810
	Evap Motor HP	1/3
	Evap Motor Watts	330
Condenser Characteristics	Condenser CFM	1010
	Condenser Motor HP	1/3
	Condenser Motor Watts	350
Miscellaneous Features	Condensate	5 gal. tank
	Sound Level	65
	R-410A Charge Oz.	37



Low Temperature Portable Air Cooled Air Conditioners

20AC 2412

Power Supply 208-230 volts 60 hertz 1 phase 14.9 amperes

Width 24 inches

Depth 30 inches

Height 45.5 inches

Weight (net/shipping) lbs 260/285

All models are backed by a 12-month warranty with 60 months for the compressor.

