



Portable Water Cooled Air Conditioners

OWC 2412

Cooling Capacity	@ARI 80°F-67°F at 52% Relative Humidity	2 Ton - 23,950
Dimensions	Width (Inches)	24.25
	Depth (Inches)	13.0
	Height (Inches)	37.5
	Weight (Pounds)	160
	Shipping Weight	180
	Shipping Volume (cubic feet)	12
Electrical Characteristics	Power Supply (Volts)	208-230/1
	Current Consumption	9.9
	Cooling Watts	2100
	In rush current (Amps)	86.5
	NEMA Plug Configuration	6-20p
	EER	11.4
	Min-max Voltage	187-253
	Power Cord Gauge	14/3
	Power Cord Length (Feet)	10
Compressor Characteristics	Compressor HP	2
	Compressor RLA	10.5
	Compressor LRA	48
Evaporator	Evap (CFM)	810
	Evap Motor HP	1/3
	Evap Motor Watts	330
Water Connection Characteristics	Cond Water Flow (GPM) at 60°F inlet	1.55
	Cond Water Flow (GPM) at 85°F inlet	6
	Cond Coil Pressure Drop PSI	0.2
	Water Valve Pressure Drop PSI	2.0
	Water Valve Connection	3/8 MF
	Drain (Return) Connection	3/8 MF
Miscellaneous Features	Condensate Pump Lift	20 Ft.
	Sound Level	60
	R-410A Charge Oz.	16



Portable Water Cooled Air Conditioners

OWC 2412

Power Supply 208-230 volts 60 hertz 1 phase 9.9 amperes

Width 24.25 inches

Depth 13 inches

Height 37.5 inches

Weight (net/shipping) lbs 160/180

All models are backed by a 12-month warranty with 60 months for the compressor.

